

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 03/02/2016 Supersedes:05/15/2015

Version: 1.2

Product identifier Product form : Trade name : Product code : 1.2. Relevant identified uses of the substant	Mixture iLAST NON-CHLOR BRAKE CLEANER 10% VOC COMPLIANT 14 OZ. FPiL0001
Product form : Trade name : Product code : 1.2. Relevant identified uses of the substance/mixture :	ILAST NON-CHLOR BRAKE CLEANER 10% VOC COMPLIANT 14 OZ.
Trade name : Product code : 1.2. Relevant identified uses of the substance/mixture Use of the substance/mixture :	ILAST NON-CHLOR BRAKE CLEANER 10% VOC COMPLIANT 14 OZ.
Product code : 1.2. Relevant identified uses of the substance/mixture Use of the substance/mixture :	
1.2. Relevant identified uses of the substance/mixture Use of the substance/mixture :	FPiL0001
Use of the substance/mixture :	
	nce or mixture and uses advised against
1.3 Details of the supplier of the sefety de	Brake Parts Cleaner
1.3. Details of the supplier of the safety da	ta sheet
Motosel Industrial Group 204 Cayer St. Coquitlam, BC V3K5B1 Canada T 888-668-6463	
1.4. Emergency telephone number	
Emergency number :	CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)
SECTION 2: Hazards identification	
2.1. Classification of the substance or mix	
GHS-US classification Flam. Aerosol 2 H223	
Compressed gas H280 Skin Irrit. 2 H315 Eye Irrit. 2A H319	
Repr. 2 H361 STOT SE 1 H370 STOT SE 3 H336	
Full text of H statements : see section 16	
2.2. Label elements	
GHS-US labeling	
	GHS02 GHS04 GHS07 GHS08
Signal word (GHS-US) :	Danger
Hazard statements (GHS-US) :	 H223 - Flammable aerosol H280 - Contains gas under pressure; may explode if heated H315 - Causes skin irritation H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H361 - Suspected of damaging fertility or the unborn child H370 - Causes damage to organs
	 P201 - Obtain special instructions P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat,sparks,open flames,hot surfaces No smoking P211 - Do not spray on an open flame or other ignition source P251 - Pressurized container: Do not pierce or burn, even after use P260 - Do not breathe dust,fumes,gas,mist,vapor spray P261 - Avoid breathing dust,fume,gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective gloves,protective clothing,eye protection,face protection P302+P352 - If on skin: Wash with plenty of soap and water P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P307+P311 - If exposed or concerned: Get medical advice/attention P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell. P321 - Specific treatment: See section 4.1 on SDS
06/03/2017	EN (English US) 1/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P410+P403 - Protect from sunlight. Store in a well-ventilated place P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
2.3.	Other hazards	
Other hazards not contributing to the classification		: Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

Name	Product identifier	%	GHS-US classification
Acetone	(CAS No) 67-64-1	70 - 85	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Carbon Dioxide, Liquefied, Under Pressure	(CAS No) 124-38-9	9-15	Compressed gas, H280
Heptane, Branched Cyclic	(CAS No) 426260-76-6	5.7504 - 5.99	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Methanol	(CAS No) 67-56-1	1 - 5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
n-Heptane	(CAS No) 142-82-5	1.4975 - 2.6955	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Toluene	(CAS No) 108-88-3	0.0599 - 0.2396	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

The exact percentage is a trade secret.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.
First-aid measures after inhalation	: Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Direct contact with the eyes is likely to be irritating. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effect	s, both acute and delayed
Symptoms/injuries	: Suspected of damaging fertility or the unborn child. Causes damage to organs.
Symptoms/injuries after inhalation	: May cause irritation or asthma-like symptoms. Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Indication of any immediate medical attention and special treatment needed No additional information available		
SECTION 5: Firefighting measures		
5.1. Extinguishing media	. Foom Drupouder Corbon diavide Water arrow Sand	
Suitable extinguishing media Unsuitable extinguishing media	 Foam. Dry powder. Carbon dioxide. Water spray. Sand. Do not use a heavy water stream. 	
5.2. Special hazards arising from the s	ubstance or mixture	
Fire hazard	: Flammable aerosol.	
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of	
	burns and injuries.	
5.3. Advice for firefighters		
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.	
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.	
Other information	: Aerosol Level 2.	
SECTION 6: Accidental release mea	asures	
6.1. Personal precautions, protective e	quipment and emergency procedures	
General measures	: No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.	
6.1.1. For non-emergency personnel		
Protective equipment	: Gloves. Safety glasses.	
Emergency procedures	: Evacuate unnecessary personnel.	
6.1.2. For emergency responders		
6.1.2. For emergency responders Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.	
Emergency procedures	: Ventilate area.	
6.2. Environmental precautions	ify authorities if liquid enters sewers or public waters.	
6.3. Methods and material for containm		
For containment	: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.	
Methods for cleaning up	: Store away from other materials.	
6.4. Reference to other sections		
See Heading 8. Exposure controls and persona	al protection.	
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed	: Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.	
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe dust,fumes,gas,mist,vapor spray.	
Hygiene measures	: Wash contaminated clothing before reuse. Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.	
7.2. Conditions for safe storage, includ	ling any incompatibilities	
Technical measures	: Proper grounding procedures to avoid static electricity should be followed.	
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.	
Incompatible products	: Strong bases. Strong acids.	
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.	
Storage area	: Store in a well-ventilated place.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.3. Specific end use(s)

Follow Label Directions.

.1. Control parar	neters	
Benzene (71-43-2)		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm
Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (mg/m ³)	75 mg/m³
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
n-Heptane (142-82-5)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm (Heptane, all isomers; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	500 ppm (Heptane, all isomers; USA; Short time value TLV - Adopted Value)
Heptane, Branched C		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
Carbon Dioxide, Liqu	efied, Under Pressure (124-38-9)	
USA ACGIH	ACGIH TWA (mg/m ³)	9000 mg/m³
USA ACGIH	ACGIH TWA (ppm)	5000 ppm (Carbon dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (mg/m ³)	54000
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm
Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (mg/m³)	1188 mg/m ³
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (mg/m ³)	1782 mg/m ³
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m ³
USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (mg/m ³)	328 mg/m ³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

Appropriate engineering controls

: Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Safety Data Sheet

ersonal protective equipment	: Gloves. Safety glasses. Avoid all unnecessary exposure.
Materials for protective clothing	: GIVE EXCELLENT RESISTANCE:
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Consumer exposure controls	: Avoid contact during pregnancy/while nursing.
Other information	: Do not eat, drink or smoke during use.
SECTION 9: Physical and chemica	properties
0.1. Information on basic physical and	chemical properties
Physical state	: Gas
Appearance	: Liquid.
Color	: Colourless to light yellow.
Ddor	: Acetone odour. Solvent-like odour.
Ddor threshold	: No data available
Н	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
felting point	: -95 °C (Lowest Component-Acetone)
reezing point	: No data available
Boiling point	: 56 °C (Lowest Component-Acetone)
Flash point	: -18 °C (Lowest Component-Acetone)
Critical temperature	: 235 °C (Lowest Component-Acetone)
Auto-ignition temperature	: 465 °C (Lowest Component-Acetone)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
/apor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.783
Solubility	: Soluble in water. Soluble in ethanol. Soluble in ether. Soluble in dimethyl ether. Soluble in petroleum spirit. Soluble in chloroform. Soluble in dimethylformamide. Soluble in oils/fats.
og Pow	: No data available
og Kow	: No data available
/iscosity, kinematic	: No data available
/iscosity, dynamic	: No data available
Explosive properties	: No data available
Dxidizing properties	: No data available
Explosion limits	: No data available
0.2. Other information	
/OC content	: 9.6 %
Gas group	: Compressed gas
SECTION 10: Stability and reactivit	y
0.1. Reactivity	
la additional information available	

No additional information available

10.2. **Chemical stability**

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3.	Possibility of hazardous reactions	
Not esta	ablished.	
10.4.	Conditions to avoid	

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

0.5. Incompatible materials	
Strong acids. Strong bases.	
0.6. Hazardous decomposition products	
oxic fume Carbon monoxide. Carbon dioxide.	
SECTION 11: Toxicological informati	on
1.1. Information on toxicological effects	
······································	
Acute toxicity	: Not classified
Benzene (71-43-2)	
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg
	bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
n-Heptane (142-82-5)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
Heptane, Branched Cyclic (426260-76-6)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit LC50 inhalation rat (mg/l)	17100 mg/kg corresponding to 20 ml/kg bw according to the authors128.2 mg/l/4h Air
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
	·····
Benzene (71-43-2) IARC group	1
Toluene (108-88-3)	
IARC group	3
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated	Causes damage to organs. May cause drowsiness or dizziness.Not classified
exposure)	
Aspiration hazard	: Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause irritation or asthma-like symptoms. Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.

Causes serious eye irritation.

SECTION 12: Ecological information	
2.1. Toxicity	
Benzene (71-43-2)	
LC50 fish 1	5.3 mg/l (LC50; 96 h; Salmo gairdneri)
EC50 Daphnia 2	10 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna
Threshold limit algae 1	100 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
n-Heptane (142-82-5)	
EC50 Daphnia 1	0.2 mg/l (LC50; Other; 96 h; Chaetogammarus marinus; Semi-static system; Salt water; Experimental value)
Acetone (67-64-1)	
EC50 Daphnia 2	12600 mg/l (LC50; Other; 48 h; Daphnia magna; Static system; Fresh water; Experimenta value)
Carbon Dioxide, Liquefied, Under Pressure	(124-38-9)
LC50 fish 1	35 mg/l (LC50; 96 h; Salmo gairdneri)
Acetone (67-64-1)	
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)
TLM fish 2	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)

Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

12.2. Persistence and degradability

LAST NON-CHLOR BRAKE CLEANER 10% VOC COMPLIANT 14 OZ.			
Persistence and degradability	Not established.		
Benzene (71-43-2)			
Persistence and degradability	Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.		
Biochemical oxygen demand (BOD)	2.18 g O ₂ /g substance		
Chemical oxygen demand (COD)	2.15 g O ₂ /g substance		
ThOD	3.10 g O ₂ /g substance		
BOD (% of ThOD)	0.70		
Toluene (108-88-3)			
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.		
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance		
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance		
ThOD	3.13 g O ₂ /g substance		
BOD (% of ThOD)	0.69		
n-Heptane (142-82-5)			
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.		
Biochemical oxygen demand (BOD)	1.92 g O ₂ /g substance		
Chemical oxygen demand (COD)	0.06 g O ₂ /g substance		
6/03/2017 EN (English LIS) 7/14			

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Heptane (142-82-5)						
ThOD	3.52 g O ₂ /g substance					
BOD (% of ThOD)	> 0.5 (5 days; Literature study)					
	> 0.5 (5 days, Literature study)					
Heptane, Branched Cyclic (426260-76-6)						
Persistence and degradability	May cause long-term adverse effects in the environment.					
	Acetone (67-64-1)					
Persistence and degradability	Not established.					
Carbon Dioxide, Liquefied, Under Pressur	e (124-38-9)					
Persistence and degradability	Biodegradability: not applicable. Not applicable (gas).					
Biochemical oxygen demand (BOD)	Not applicable					
Chemical oxygen demand (COD)	Not applicable					
ThOD	Not applicable					
Acetone (67-64-1)						
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under					
	anaerobic conditions. No (test)data on mobility of the substance available. Not established.					
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance					
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance					
ThOD	2.20 g O ₂ /g substance					
BOD (% of ThOD)	(20 day(s)) 0.872					
Methanol (67-56-1)						
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.					
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance					
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance					
ThOD	1.5 g O ₂ /g substance					
BOD (% of ThOD)	0.8 (Literature study)					
12.3. Bioaccumulative potential						
iLAST NON-CHLOR BRAKE CLEANER 10	% VOC COMPLIANT 14 OZ.					
Bioaccumulative potential	Not established.					
Benzene (71-43-2)						
BCF fish 1	19 (BCF)					
BCF fish 2	< 10 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 3 days; Leuciscus idus; Flow-through system; Fresh water; Experimental value)					
BCF other aquatic organisms 1 30 (BCF; 24 h; Chlorella sp.)						
Log Pow	2.13 (Experimental value)					
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).					
Toluene (108-88-3)						
BCF fish 2	90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water)					
Log Pow	2.73 (Experimental value; Other; 20 °C)					
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).					
n-Heptane (142-82-5)						
BCF other aquatic organisms 1	552 (BCF; BCFBAF v3.00)					
Log Pow	4.66 (Experimental value; 4.5; Literature study)					
Bioaccumulative potential	Potential for bioaccumulation ($4 \ge Log \text{ Kow} \le 5$).					
Heptane, Branched Cyclic (426260-76-6)						
Bioaccumulative potential	Not established.					
Acetone (67-64-1)						
Bioaccumulative potential	Not established.					
Carbon Dioxide, Liquefied, Under Pressur						
Log Pow	0.83 (Experimental value)					
Bioaccumulative potential	Bioaccumulation: not applicable.					
Acetone (67-64-1)						
BCF fish 1	0.69 (Pisces)					
BCF other aquatic organisms 1	3					
Log Pow	-0.24 (Test data)					
Bioaccumulative potential	Not bioaccumulative. Not established.					
Methanol (67-56-1) BCF fish 1 < 10 (BCF; 72 h; Leuciscus idus)						
03/2017 EN (English US) 8/14						

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mathemat (CZ EC 4)					
Methanol (67-56-1)					
Log Pow	-0.77 (Experimental value; Other)				
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).				
2.4. Mobility in soil					
Benzene (71-43-2)					
Surface tension	0.029 N/m (20 °C)				
Log Koc	Koc,134.1; QSAR				
Toluene (108-88-3)					
Surface tension	0.03 N/m (20 °C)				
n-Heptane (142-82-5)					
Surface tension	0.019 N/m (25 °C; 0.020 N/m; 20 °C)				
Log Koc	log Koc, SRC PCKOCWIN v2.0; 2.38; Calculated value				
Acetone (67-64-1)					
Surface tension	0.0237 N/m (20 °C)				
Methanol (67-56-1)					
Surface tension 0.023 N/m (20 °C)					
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value				
2.5. Other adverse effects					
ther information	: Avoid release to the environment.				
ECTION 13: Disposal consideration	ns				
3.1. Waste treatment methods					
Vaste disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.				
dditional information	: Flammable vapors may accumulate in the container.				
cology - waste materials	Avoid release to the environment.				
ECTION 14: Transport information					
accordance with ADR / RID / IMDG / IATA / /	AUN				
S DOT (ground): UN1950, Aerosols, 2.	1, Limited Quantity				

US DOT (ground):	UN1950, Aerosols, 2.1, Limited Quantity
ICAO/IATA (air):	UN1950, Aerosols, 2.1, Limited Quantity
IMO/IMDG (water):	UN1950, Aerosols, 2.1 (Marine Pollutant-Heptane), Limited Quantity
Special Provisions:	N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols

14.2. UN proper shipping name				
Proper Shipping Name (DOT)	: Aerosols Flammable, (each not exceeding 1 L capacity)			
Class (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115			
Hazard labels (DOT)	: 2.1 - Flammable gas			
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols			
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306			
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None			
DOT Packaging Bulk (49 CFR 173.xxx)	: None			
14.3. Additional information				
Other information	: No supplementary information available.			

Overland transport

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea					
OT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel					
DOT Vessel Stowage Other	48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials				
Subsidiary risks (IMDG)	Marine Pollutant-Heptane				
Air transport					
DOT Quantity Limitations Passenger aircraft/rail : (49 CFR 173.27)	75 kg				
DOT Quantity Limitations Cargo aircraft only (49 : CFR 175.75)	150 kg				
SECTION 15: Regulatory information					
15.1. US Federal regulations					
iLAST NON-CHLOR BRAKE CLEANER 10% V	DC COMPLIANT 14 OZ.				
SARA Section 311/312 Hazard Classes Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard Sudden release of pressure hazard					
Benzene (71-43-2)					
Listed on the United States TSCA (Toxic Substar Subject to reporting requirements of United State					
Toluene (108-88-3)					
Subject to reporting requirements of United State Listed on the United States TSCA (Toxic Substar Listed on the United States SARA Section 302	s SARA Section 313 nces Control Act) inventory				
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard				
Heptane, Branched Cyclic (426260-76-6)					
Listed on the United States TSCA (Toxic Substar	nces Control Act) inventory				
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard				
Carbon Dioxide, Liquefied, Under Pressure (1	24-38-9)				
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard				
Acetone (67-64-1)					
Listed on the United States TSCA (Toxic Substar Subject to reporting requirements of United State					
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard				
Methanol (67-56-1)	·				
Subject to reporting requirements of United State Listed on the United States TSCA (Toxic Substar Listed on the United States SARA Section 302 Listed on the United States SARA Section 355					
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard				
15.2. International regulations CANADA					
ILAST NON-CHLOR BRAKE CLEANER 10% V	OC COMPLIANT 14 OZ.				
WHMIS Classification	Class B Division 5 - Flammable Aerosol				
Benzene (71-43-2)					
Listed on the Canadian DSL (Domestic Substanc	es List)				
Toluene (108-88-3)					
Listed on the Canadian DSL (Domestic Substance	es List)				
WHMIS Classification Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects					

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Heptane, Branched Cyclic (426260-76-6)				
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects			
Acetone (67-64-1)	Acetone (67-64-1)			
Listed on the Canadian DSL (Domestic Substances List)				
WHMIS Classification	Class B Division 2 - Flammable Liquid			
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects			
Methanol (67-56-1)				
Listed on the Canadian DSL (Domestic Substances List)				
WHMIS Classification	Class B Division 2 - Flammable Liquid			
	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects			
	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects			
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects			

EU-Regulations

Toluene (108-88-3)		
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)		
Heptane, Branched Cyclic (426260-76-6)		
Acetone (67-64-1)		
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)		
Methanol (67-56-1)		
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)		

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11 Xn; R20/21/22 Xn; R68/20/21/22 Xi; R36 Full text of R-phrases: see section 16

15.2.2. National regulations

Benzene (71-43-2)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Toluene (108-88-3)
Heptane, Branched Cyclic (426260-76-6)
All components are either listed on the US TSCA Inventory, or are not regulated under TSCA under 40 CFR 720.30.
Acetone (67-64-1)

Acetone (67-64-1)

Methanol (67-56-1)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

ILAST NON-CHLOR BRAKE CLEANER 10% VOC COMPLIANT 14 OZ.		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive	No	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

iLAST NON-CHLOR BR	AKE CLEANER 10% VOC COM	IPLIANT 14 OZ.		
Toxicity - Male				
State or local regulations		U.S California - Proposition	65	
Benzene (71-43-2)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	Yes	No	Yes	
Toluene (108-88-3)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	
n-Heptane (142-82-5)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Heptane, Branched Cyc				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Acetone (67-64-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Carbon Dioxide, Liquefi	ed, Under Pressure (124-38-9)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Acetone (67-64-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	
Methanol (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	
Benzene (71-43-2) State or local regulation U.S California - Proposi U.S Pennsylvania - RTH	ition 65 K (Right to Know) List			
New Jersey Right-to-Know	w			
Toluene (108-88-3) State or local regulation				
U.S California - Proposi	ition 65			
06/03/2017		oglish LIS)		12/14

EN (English US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. //, No. 58 / Monday, March 26, 2012 / Rules and Regulations	
Toluene (108-88-3)	
U.S New Jersey - Special Health Hazards Substances List New Jersey Right-to-Know U.S Massachusetts - Right To Know List Rhode Island Right to Know U.S Michigan - Critical Materials List U.S New Jersey - Environmental Hazardous Substances List U.S New Jersey - Environmental Hazardous Substances List U.S Illinois - Toxic Air Contaminants U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
Acetone (67-64-1)	
State or local regulations	
U.S California - Proposition 65 Benzene 71-43-2 U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List	
Methanol (67-56-1)	
State or local regulations	
U.S California - Proposition 65 New Jersey Right-to-Know Florida Right to Know U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List	

SECTION 16: Other information

: None.

Other information Full text of H-phrases:

H223 Flammable aerosol H224 Extremely flammable liquid and vapor H225 Highly flammable liquid and vapor H280 Contains gas under pressure; may explode if heated Toxic if swallowed H301 H304 May be fatal if swallowed and enters airways H311 Toxic in contact with skin H315 Causes skin irritation Causes serious eye irritation H319 H331 Toxic if inhaled May cause drowsiness or dizziness H336 H361 Suspected of damaging fertility or the unborn child H370 Causes damage to organs H373 May cause damage to organs through prolonged or repeated exposure H400 Very toxic to aquatic life H410 Very toxic to aquatic life with long lasting effects H412 Harmful to aquatic life with long lasting effects

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 1 Slight Hazard
Personal Protection	: В

SDS US (GHS HazCom 2012) - TCC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.